

???????????? DAIKIN ????? ????? FCAG71B / RZASG71MV1 24000 btu



???????????? DAIKIN ????? ????? FCAG71B / RZASG71MV1 24000 btu



???????????? DAIKIN ????? ?????? FCAG71B / RZASG71MV1 24000 btu

????????????: ??? ?????????????? ?????
????

????????? ??? ?? ??????

??????????

????????????????????? ??????????????

Efficiency data												
	FCAG + RZASG											
	71B + 71MY1		100B + 100MY1		125B + 125MY1		140B + 140MY1		125B + 125MY1		140B + 140MY1	
Cooling capacity	Nom.	kW	6.80	9.50	12.1	13.4	9.50	12.1	13.4	15.5		
Heating capacity	Nom.	kW	7.50	10.8	13.5	15.5	10.8	13.5	15.5	15.5		
Space cooling	Tenancy efficiency class	Pdesign	A++				A++					
	Capacity	kW	6.80	9.50	12.1	13.4	9.50	12.1	13.4			
	SEER		6.47	6.55	5.76	6.53	6.55	5.76	6.53			
	Ƞfc	%	-	-	227	298	-	227	298			
	Annual energy consumption	kWh/a	368	-	507	1,261	507	1,261	507	1,261		
Space heating		A	A+				A+					
Average climate	Capacity	kW	4.50	6.00	7.80	8.00	6.00	8.00	8.00			
	SCOP/A		4.00	4.17	4.05	4.31	4.17	4.05	4.31			
	Ƞsh	%	-	-	159	169	-	159	169			
	Annual energy consumption	kWh/a	1,575	2,016	2,074	2,334	2,016	2,074	2,334			
Indoor unit	Dimensions	mm	1440x710x140	1060	1250	1400	1060	1250	1400	1400		
	Unit	HeightWidthDepth	mm	2040x40x840	1060	1250	1400	1060	1250	1400		
	Weight	kg	21	24								
Air filter	Type											
Desiccant panel	Model											
	Dimensions	HeightWidthDepth	mm	Standard panels: BYC0140E - white with grey louvers / BYC0140EW - full white / BYC0140B - black								
Fan	Weight	kg	Standard panels: 50x950x950 / Auto cleaning panels: 50x950x950 / Designer panels: 50x950x950									
	Air flow rate	mm/min	9.3/12.5/15.3	12.4/17.6/22.8	17.4/19.2/26.0	12.4/17.6/22.8	17.4/19.2/26.0	12.4/17.6/22.8	17.4/19.2/26.0			
	Cooling	Low/Medium/High	mm/min	9.1/12.1/15.0	12.4/17.6/22.8	17.4/19.2/26.0	12.4/17.6/22.8	17.4/19.2/26.0	12.4/17.6/22.8			
	Heating	Low/Medium/High	mm/min	9.1/12.1/15.0	12.4/17.6/22.8	17.4/19.2/26.0	12.4/17.6/22.8	17.4/19.2/26.0	12.4/17.6/22.8			
Sound power level	Sound pressure level	dB(A)	51	54	58	54	58	54	58			
	Cooling	Low/High	dB(A)	51	54	58	54	58	54			
	Heating	Low/High	dB(A)	28/35	29/37	29/41	29/37	29/41	29/41			
Control systems	Indirect remote control											
	Wired remote control											
Power supply	Phase/Frequency/Voltage	Hz/V	BRCH1519W/X/R / BRCT153A/R/C / BRCT052									
			1~50/60/220/240/220									
Outdoor unit	Dimensions	HeightWidthDepth	mm	770x600x420	1000	1250	1400	1000	1250	1400		
	Unit	HeightWidthDepth	mm	770x600x420	1000	1250	1400	1000	1250	1400		
	Weight	kg	60	70	78	70	70	70	70	72		
	Sound power level	dB(A)	65	70	71	73	70	71	73			
	Sound pressure level	dB(A)	46	53	54	53	54	53	54			
Operation range	Cooling	Nom.	dBA	47		57						
	Heating	Nom.	dBA	47		57						
	Type/GWP											
Refrigerant	Chlorine	kg/T025	2.45/1.65	2.60/1.76	3.00/1.90	2.60/1.76	2.60/1.76	2.60/1.76	2.60/1.76			
Piping connections	Liquid/Gas	OD	mm	12	15	15	12	15	15			
	Piping length	OU-IU	m	Max.	System	Equivalent	Max.	System	Equivalent			
			m	10	10	10	10	10	10			
			m	30	30	30	30	30	30			
	Additional refrigerant charge	t/t-OU	kg/m	See installation manual								
	I-OU	Max.	kg/m	30.0								
Power supply	Phase/Frequency/Voltage	Hz/V	1~50/60/220/240									
	Current - 50Hz	Maximum fuse amps (MFA)	A	20	25	32	20	25	32	16		

?????? ????????

?? ?????????? ?????????????? ?? ?? ??????? ????????